

**STANDARD DEPARTURE ROUTES – INSTRUMENT (SID) RWY 25**

SID	ROUTING AND ALTITUDES	MIN. CLIMB GRAD.
<b>ALIKA 2D</b>	<p><b>ALIKA TWO DELTA</b> Climb runway heading (MAG Track 254°) to FL90 or above. At 1500 FT turn <b>right MAG Track 300°</b> to intercept and follow <b>RDL 270° KTS</b> (MAG Track 270°) inbound ALIKA. Do not turn before the DER. <b>IAS Max</b> during the turns <b>250 Kt.</b></p>	<b>4.0% up to 4000 FT</b>
<b>NEDEK 2D</b>	<p><b>NEDEK TWO DELTA</b> Climb runway heading (MAG Track 254°) to 7000 FT or above. Then intercept and follow <b>RDL 250° KTS</b> (MAG Track 250°) inbound NEDEK. Do not turn before the DER. <b>IAS Max</b> during the turns <b>250 Kt.</b></p>	
<b>LOBIN 2D</b>	<p><b>LOBIN TWO DELTA</b> Climb runway heading (MAG Track 254°) to FL90 or above. At 1500 FT turn <b>right</b> to intercept and follow <b>RDL 312° KTS</b> (MAG Track 132°) inbound KTS. Then proceed to <b>LOBIN RDL 083° KTS</b> (MAG Track 083°). Do not turn before the DER. <b>IAS Max</b> during the turns <b>250 Kt.</b></p>	